## Prole<sup>®</sup>



## PB26 Series 3.96mm(.156") Friction Lock Breakaway Headers

- O Available with kinked pins for better PC board retention
- O Available with straight and right angle tails
- Available with flat back wall for polarization
- O Compatible with most 3.96mm pitch connectors in the market


## Construction


- O Insulator: Glass filled Polyester UL 94V-0, Color White
- With Tin plated 1.14mm square pin
- O Engineering No's: CI82 Series






**N**:E159616






- $A = 3.96 \times No. \text{ of Spaces}$ B = A + 3.96
- \* Available in 2 through 24 circuits







Recommended P.C. Board Layout




P/N: PB26\*\*P\*V00L




- $A = 3.96 \times No. \text{ of Spaces}$
- B = A + 3.96
- \* Available in 2 through 24 circuits





Recommended P.C. Board Layout



## **Ordering Code**

**O** PB26

**2** 

**3** 

**4** 

5 V **6** 

- 1 Series No.
- No. of Circuits: 02 to 24
- 3 P= Pin header
- 4 Plating code:
  - 1= Tin over Nickel plated
  - \* Optional plating available but MOQ requested
- **6** Type: V= Straight
  - H= Right angle
- **6** Other options:

00= Color White, With Locking Ramp (Standard)
0L= Color White, Without Locking Ramp

\* Special options Consult factory